






## DW-VFDPT10

No.	Category	Description																																									
1	Full plastic inline duct fan																																										
2	<b>Description</b>	Full plastic construction																																									
3	<b>Type</b>	Inline duct fan																																									
4	<b>Certificate</b>	CB, CE																																									
5	<b>Input Voltage/Hz</b>	110V/60Hz																																									
6	<b>Duct Size</b>	4"/100mm																																									
7	<b>Motor</b>	Capacitor motor, 100% copper coil																																									
8	<b>Bearing</b>	Ball bearing																																									
9	<b>Thermal cut-out protection</b>	Yes																																									
10	<b>Speed</b>	Optional speed: single speed, 2 speed, 3 speed available																																									
11	Hi	<b>Power</b>	33W																																								
12		<b>Air volume</b>	198m <sup>3</sup> /h																																								
13		<b>Noise</b>	56																																								
14		<b>RPM</b>	2350																																								
15		<b>Pressure</b>	140																																								
16	Mi	<b>Power</b>	24W																																								
17		<b>Air volume</b>	138m <sup>3</sup> /h																																								
18		<b>Noise</b>	46																																								
19		<b>RPM</b>	1750																																								
20	Low	<b>Pressure</b>	110																																								
21		<b>Power</b>	22W																																								
22		<b>Air volume</b>	120m <sup>3</sup> /h																																								
23		<b>Noise</b>	41																																								
24		<b>RPM</b>	1500																																								
25	<b>Pressure</b>	90																																									
26	<b>Material</b>	PP fan body, ABS blade																																									
27	<b>Application area</b>	12~16m <sup>2</sup>																																									
28	<b>Protection Grade</b>	IPX2																																									
29	<b>Mounting</b>	Ceiling mounted																																									
30	<b>Gross weight per carton</b>	14.6																																									
31	<b>Package</b>	68.1x32.4x48.6cm (6pcs/ctn)																																									
32	Dimension Picture	<div style="display: flex; align-items: center; justify-content: center;">  <table border="1" style="margin-left: 20px;"> <thead> <tr> <th rowspan="2">Model</th> <th colspan="4">Dimensions mm</th> <th colspan="2">Installation mm</th> </tr> <tr> <th>A</th> <th>B</th> <th>C</th> <th>D</th> <th>E</th> <th>F</th> </tr> </thead> <tbody> <tr> <td>DW-VFDPT10</td> <td>258</td> <td>ø99</td> <td>216</td> <td>178</td> <td>80</td> <td>60</td> </tr> <tr> <td>DW-VFDPT12</td> <td>258</td> <td>ø123</td> <td>216</td> <td>178</td> <td>80</td> <td>60</td> </tr> <tr> <td>DW-VFDPT15</td> <td>304</td> <td>ø148</td> <td>248</td> <td>204</td> <td>93</td> <td>60</td> </tr> <tr> <td>DW-VFDPT20</td> <td>300</td> <td>ø196</td> <td>275</td> <td>210</td> <td>114</td> <td>85</td> </tr> </tbody> </table> </div>	Model	Dimensions mm				Installation mm		A	B	C	D	E	F	DW-VFDPT10	258	ø99	216	178	80	60	DW-VFDPT12	258	ø123	216	178	80	60	DW-VFDPT15	304	ø148	248	204	93	60	DW-VFDPT20	300	ø196	275	210	114	85
Model	Dimensions mm				Installation mm																																						
	A	B	C	D	E	F																																					
DW-VFDPT10	258	ø99	216	178	80	60																																					
DW-VFDPT12	258	ø123	216	178	80	60																																					
DW-VFDPT15	304	ø148	248	204	93	60																																					
DW-VFDPT20	300	ø196	275	210	114	85																																					
33	Performance curve	 <p style="text-align: center; color: red; font-size: small;">DPT10-23-1</p>																																									